



ICPC Recommendation

Recommendation No. 9

Minimum Technical Requirements for a Desktop Study (also known as Cable Route Study)

Contact for Enquiries and Proposed Changes

If you have any questions regarding this document or suggestions for improving it, please contact:

International Cable Protection Committee Ltd
PO Box 150
Lymington
SO41 6WA
United Kingdom

Secretary: **Mr. Graham Marle**
Tel: **+ 44 1590 681 673**
Fax: **+44 870 432 7761**
E-mail: **secretary@iscpc.org**
ICPC Web-site: **www.iscpc.org**

DISCLAIMER

An International Cable Protection Committee Ltd ("ICPC") Recommendation ("Recommendation") implies a consensus of those substantially concerned with its scope and provisions. A Recommendation is intended as a guide to aid cable owners and other seabed users in promoting the highest goals of reliability and safety in the submarine cable environment. The existence of a Recommendation does not in any respect preclude anyone, whether he has approved the Recommendation or not, from laying or repairing undersea cables or employing procedures to these ends which may be required by the ordinary practice of seamanship or by the special circumstances of each case, but which may not be conforming to the Recommendation.

The ICPC does not develop standards and will in no circumstances give an interpretation of a Recommendation in the name of the ICPC. The ICPC and its members do not accept any liability for any errors in the Recommendation or for any consequences resulting from its use as a planning guide. Nothing in this Recommendation should be viewed as relieving anyone from the rights and obligations of seabed users under international law, including but not limited to the United Nations Convention of the Law of the Sea ("UNCLOS").

NB: ICPC Recommendations are subject to periodic review and users are cautioned to obtain the latest issues. This Recommendation may be revised or withdrawn at any time without further notice to the recipient.

TABLE OF CONTENTS

Disclaimer	2
Table of Contents	3
1. Introduction	4
2. Desktop Study – Minimum Requirements	4
2.1 Overview	4
2.2 Content.....	4
2.2.1 Routing Selection and Landing	4
2.2.2 Geology	5
2.2.3 Climatology	6
2.2.4 Seismology	6
2.2.5 Oceanography	6
2.2.6 Commercial Operations, Restricted Areas and Obstructions	7
2.2.7 Biological Factors.....	8
2.2.8 Regulatory Factors.....	8
2.3 Site Visit	8
2.4 Route Recommendation	10
2.5 Survey Recommendation.....	10
2.6 Reporting and Documentation.....	11
2.6.1 Regular Status Reports	11
2.6.2 The Preliminary Site Visit Report	11
2.6.3 Desktop Study Report.....	12
2.6.4 Digital Format of DTS Report.....	13
2.6.5 DTS Report Quantities	13
2.7 Charting Requirements	13
2.7.1 Description	13
2.7.2 Chart Scales	14
3. References	16
4. Definitions	16
5. Attachments.....	16
6. Acknowledgements	16

1. INTRODUCTION

A Desktop Study (DTS) is an essential prerequisite to a detailed submarine cable route survey. Properly performed, the DTS and the Marine Route Survey will identify the safest and most technically viable route for use in the engineering, construction, installation and subsequent maintenance a submarine cable system.

This ICPC Recommendation sets out the minimum technical requirements of a Desktop Study in order to ensure the above requirements are satisfactorily met.

[Note: A Desktop Study is also known as a Cable Route Study]

2. DESKTOP STUDY – MINIMUM REQUIREMENTS

2.1 Overview

The Desktop Study is the first major step in the overall route design process (a Route Feasibility Study may have previously been undertaken to study the route concept). It is the foundation on which the subsequent marine survey is built and adequate time must be allowed for the DTS to be properly conducted if an optimum route for the proposed submarine cable system is to be identified.

Failure to complete a thorough DTS will inevitably result in increased survey and marine installation costs and impact on the scheduled Ready for Service (RFS) date of the system. A deficient DTS may result in installation delays, route diversions, changes in landing site or, in the worse case, poor system reliability.

Identification of the requirements for permits to conduct both the surveys and also the actual cable installation is a critical component of the DTS. Failure to obtain all the correct permits for a survey can result in extensive delays with expensive resources being placed on standby until the permit issues are resolved.

2.2 Content

The DTS should include, but not be limited to, to the following subject matter and shall examine their impact on the planning (including the route surveys), installation (including the land and marine based facilities) and the operation of the cable system.

2.2.1 Routing Selection and Landing

One of the intents of a DTS is to validate the proposed route between the chosen landing points of the new submarine cable system, particularly the inshore sections. Whilst the DTS may highlight the need to make relatively minor changes to the location of the landing points, the landing points are usually constrained by the location of existing land based telecommunications infrastructure, other interconnecting cable systems, the existence of cable corridors, international boundaries and/or disputed territorial claims and other geopolitical issues, and the general coastal bathymetry. In more recent times, the ability to obtain the required landing permits in the required timeframe has often had a critical role to play in landing point selection. As such, the DTS should examine the permit process for

previous cable systems, where possible, in order to ascertain likely permitting problems. Permit conditions applicable to other recently installed sea structures, such as pipelines, should also be examined.

The importance of thoroughly investigating permitting requirements as early as possible in the DTS cannot be overstated.

Prior to commencing the DTS, it is essential that the fundamental owner requirements are fully understood and any constraints noted. Failure to do so will most likely result in rework being required at a later date with attendant delays in overall project timing.

However, it must also be remembered that the overall purpose of the DTS is for specialists to design a route, initially using the fundamental owner requirements, which represents the most appropriate technical and environmental solution.

2.2.2 Geology

The DTS should include research on regional level information to provide a broad perspective of the geological risks to the cable. This should include, but not be limited to, examination of:

- (a) the tectonic setting and associated seafloor morphology and lithology,
- (b) geological history,
- (c) seismicity,
- (d) surface faulting,
- (e) turbidity currents,
- (f) sediment transport,
- (g) sand waves,
- (h) coral reefs (tropical and cold water),
- (i) volcanic activity,
- (j) beach and near shore seabed stability: this includes determining the nature and composition of beach and nearshore soils as well as examining indicators of shoreline instability such as the presence of offshore bars, washouts, beach erosion and slumping,
- (k) Offshore geology and burial assessment: this includes sections along the proposed routing where cable burial will probably be required (i.e. high levels of activity/external aggression) and where soils are likely to prove good/difficult for cable burial. To this end, where feasible, details of likely soil shear strength, the presence of steep slopes, rock outcrops, ridges, ravines, side slopes and sea mounts along the shallow water sections of the route should be obtained in order to assess whether the chosen route is suitable for burial, and
- (l) other geohazards, not covered in above sections.

2.2.3 Climatology

In order to assist in scheduling route survey and installation activities, the DTS should include, but not be limited to, research on:

- (a) seasonal variations in climate and weather on a regional basis for the area adjacent to and along the proposed cable route.
- (b) examination of the major climatological controls, such as monsoons, convergence zones and the like, temperatures, rainfall, winds and the seasonality and frequency of gales, storms, hurricanes and the like
- (c) proximity to flood prone areas.

Due consideration should be given to any recorded changes in climate or weather patterns in recent years.

2.2.4 Seismology

The DTS should include an examination of all existing data on seismic events in order to identify.

- (a) Earthquakes (including locations, dates and magnitude)
- (b) Tsunamis
- (c) Sub-sea volcanos (including location and dates of eruption)

2.2.5 Oceanography

The DTS should include, but not be limited to, an examination of all existing data to identify.

- (a) typical sea states experienced in the region of interest
- (b) surface, midwater and bottom currents
- (c) bottom water temperatures
- (d) wind and wave data (including wave height and dominant wind directions)
- (e) other environmental anomalies that may affect survey and installation (eg sea fog if applicable)
- (f) Mean seawater levels at the planned landings and at pertinent areas along the route
- (g) Tidal levels and variations at the landings and at pertinent areas along the planned route
- (h) Tidal streams and currents (in order to determine the optimum direction of installation)
- (i) Local and seasonal variations and microclimate existence and effects

2.2.6 Commercial Operations, Restricted Areas and Obstructions

The DTS should examine all existing information pertaining to existing or planned commercial operations, restricted areas and obstructions in the vicinity of the proposed cable route and landings. The factors to be addressed should include, but not be limited to:

- (a) General shipping patterns (including shipping lanes and anchorage areas),
- (b) Restricted areas (full-time or part-time) such as;
 - ✓ anchorages,
 - ✓ mined areas,
 - ✓ military exercise areas,
 - ✓ controlled shipping channels,
 - ✓ dumping grounds (chemical/industrial wastes, explosives, radioactive materials) either in use, abandoned or planned,
 - ✓ protected areas such as coral reefs (including cold water corals*), marine sanctuaries and national parks (it is imperative that landing area seasonal constraints due to nesting birds and animals, migrating whales and dolphins, schooling fish, etc are thoroughly investigated),
 - ✓ culturally significant sites and
 - ✓ tourist attractions.

* Note: UNEP (United Nations Environment Program) have advised the ICPC that cold-water corals thrive in water temperatures between 4°C and 13°C. The ICPC have agreed with UNEP that it would be very useful if submarine cables could be included as one of the layers in UNEP-WCMC IMAPS (Interactive Map Services). This would help to identify those areas where submarine cables and coral reefs are in close proximity. IMAPS is an openly accessible resource that can be found at: http://www.unep-wcmc.org/imaps/imaps_index.htm

- (c) Commercial and Research activities such as;
 - ✓ commercial fishing activities (current and future),
 - ✓ offshore petroleum leases (current and future) that may require the construction of in-field or platform to shore transmission pipelines or umbilicals,
 - ✓ pipelines (current and planned),
 - ✓ other submarine cables (out-of-service and in-service, both current and planned in the vicinity of the proposed route) and their fault history, with tabulated information on the crossed systems name, cable type, position, water depth and angle at the crossing point and, where possible, distance to the crossed systems underwater plant, (i.e. repeaters and equalisers),
 - ✓ plans to remove existing out-of-service submarine cables,

- ✓ fish aggregation devices,
 - ✓ oceanographic and weather buoys,
 - ✓ dredging activities,
 - ✓ submarine resource development (including deep sea mining), and
 - ✓ coastal construction projects such as new port facilities, outfalls and intake structures
- (d) Other obstructions such as shipwrecks, artificial reefs and the like,
- (e) Known security threats and piracy, or political groups that may pose security risks (including ‘non friendly’ countries or unstable governments).

2.2.7 Biological Factors

The DTS should examine all information pertaining to biological factors that could have an impact on the proposed cable project. These factors include, but are not limited to:

- (a) Flora and fauna (particularly endangered and protected species) located at the proposed landings
- (b) Seabed communities including shellfish, crustaceans and coral
- (c) Fish and crustacean spawning grounds and nursery areas
- (d) Local and migratory bird populations
- (e) Marine mammals

2.2.8 Regulatory Factors

The DTS should carefully examine and provide information about the laws and regulations of the region such as:

- (a) Limits of national/territorial waters (TW), Contiguous Zone (CZ) and Exclusive Economic Zone (EEZ), as applicable, and details of disputed waters and maritime boundaries, and marine sanctuaries, where relevant,
- (b) Statutory requirements for both marine and land based activities such as environmental studies and reports, permits (installation and operating), visas, equipment importation etc, which should be both described and summarised in a permit matrix or table for ease of reference,

2.3 Site Visit

The DTS shall include reports of site visits to the primary Landing Points as well as, where possible/practical, alternate Landing Points. The site visit(s) shall examine;

- (a) the existing infrastructure for landing and terminating a submarine cable,

- (b) suitable locations to land the submarine cable and construct new suitable landing facilities (for example beach manholes, system earthing facilities and ducts), if no existing infrastructure exists (include lat/long positions and photographs of the area in the DTS report),
- (c) existing utilities that may conflict with proposed routing,
- (d) the geology to provide a geotechnical analysis of the landing sites which will aid in the design, construction or improvement of any proposed landing facilities,
- (e) shore end protection measures required (i.e. articulated pipe, directional drilling etc),
- (f) marine and terrestrial constraints, that may determine whether the cable landing is to be direct from the main lay cableship or a separate shore end installation,
- (g) security issues that may constrain operations at the proposed landing,
- (h) the climate and weather and its potential impact on the construction, durability and landing of the cable into any proposed landing facilities,
- (i) all environmental aspects, both natural and man-made, which will impact on or be impacted by the implementation of any proposed landing facilities and the subsequent installation of the cable system,
- (j) all local organisations and authorities, including local fishing organisations, that will need to be liaised with during the planning, construction and operation of any proposed landing facilities and the installation, operation and maintenance of the cable system on both the land and marine routes within the Territorial Waters and possibly Exclusive Economic Zone (EEZ) or Continental Shelf of each landing site,
- (k) conditions applicable to permits for previous cable systems installed at each Landing Point and assess their relevance to the proposed cable system,
- (l) information on other seabed users and interested parties who could potentially oppose a permit application at a specific Landing Point and the stance that such groups could be expected to take.

The DTS should also include a Shore End Landing Site Inspection report that should, as a minimum, include such data as:

- (m) Area, site and beach descriptions (of all alternate landings investigated)
- (n) Site accessibility (roadway width, surface, etc)
- (o) Working space assessments
- (p) Tides, weather, sea, swell information
- (q) Potential for beach erosion during severe storms
- (r) Marine traffic and fishing activity
- (s) Beach utilisation by public (and implications of applying access restrictions during laying operations)

- (t) Communications (radio permits, cell phone/mobile signal strengths)
- (u) Local facilities (civil contractor availability, shore end support, divers, hotels, etc)
- (v) General facilities (airport, taxis, local ports, truck hire, etc)

It is recommended the DTS Contractor, the Supplier and the Purchasers Representative should all be present during site visits where practicable.

2.4 Route Recommendation

Based on the information acquired from the site visits and desktop investigative work the DTS shall recommend at least one appropriate cable route which, to the extent feasible, avoids any hazards and meets the cable burial requirements.

The recommended route should ensure that crossings of existing pipelines and cables follow applicable ICPC Recommendations as well as consider the future maintenance of the planned cable as well as existing or planned infrastructure.

The DTS should also provide a proposed route position list (RPL) and, where possible, a Straight Line Diagram (SLD).

The route recommendations shall include, but not be limited to the following details.

- (a) Route position shown in latitude and longitude based on WGS84.
- (b) Type of landing, such as, beach excavation or directional drilled conduits,
- (c) Seabed depths,
- (d) Initial cable engineering recommendations such as cable types and quantities, slack and definition of areas where cable should be buried for protection and the depth of burial,
- (e) Route Engineering recommendations resulting from, for example, slope angles, seabed feature avoidance, burialability, existing regional fault history and alter course angles (which should ideally not exceed 25 degrees)

2.5 Survey Recommendation

The DTS shall provide recommendations for suitable terrestrial and marine surveys to accurately define the proposed route and for determining the precise route length, appropriate types and quantities of cable and installation and burial requirements.

The DTS shall provide, where possible, geodetic parameters, methodology and example computations of all transformations required to transform the proposed route WGS84 geographical co-ordinates into National Mapping Parameters for all landing sites and/or other appropriate areas as required by National Mapping Agencies/Government Organisations.

The recommendation should include, but not be limited to, the equipment and techniques required for the collection and collation of the following types of data.

- (a) Bathymetry,

- (b) Seabed and Sub-seabed Features,
- (c) Seabed Temperatures,
- (d) Ocean Currents,
- (e) Cable Burial Assessment (DTS to specify recommended equipment & techniques to be used. These should comprise a combination of geotechnical and geophysical equipment and techniques.)
- (f) Topographic and Geotechnical data for each landing,
- (g) Survey swathe widths
- (h) Areas on the route where further route development may be necessary during the survey

2.6 Reporting and Documentation

The DTS shall provide for the following reports.

2.6.1 Regular Status Reports

Regular Status Reports (timing to be agreed between contractor and client) should be provided to the client from the date of execution of the Contract up until the completion of the DTS. It is recommended that the Regular Status Reports should include, but not be limited to;

- (a) Current Plan of Work,
- (b) Update on the progress of significant events such as site visits and the Desktop Study Report and,
- (c) Advice on the key issues noted during site visits or desktop research, which may impact on the choice of landings or routing of the proposed cable and,
- (d) Progress against the baseline plan of work, critical path items and any items that may impact the finishing the DTS on schedule.

2.6.2 The Preliminary Site Visit Report

The Preliminary Site Visit Report, if required by the client, should be provided to the client within the duration agreed between the contractor and client. (Note that it may be decided that the contents of such a Report be included within the DTS as per Section 2.3.)

If required, the Preliminary Site Visit Report shall include, but not be limited to;

- (a) Summary of observations with regard to the requirements listed above [including photographs, geo-referenced beach sketches and GPS measurements of proposed BMH position and other salient features],
- (b) List of people and authorities, particularly local fishing organisations, visited and nature of discussions with or advice from these parties,

- (c) List of follow-on actions to be taken by as part of the desktop research and,
- (d) List of recommended actions such as initiating environmental approvals with relevant local authorities.

2.6.3 Desktop Study Report

The Desktop Study Report shall provide detailed information on all the issues specified above and shall be structured along the lines of the following format. Emphasis should be given to the provision of relevant maps, diagrams, charts, figures, tables and photographs in order to add clarity to the report.

- (a) Introduction
- (b) Executive Summary (to include a tabulated Risk Analysis/Summary, which identifies mitigation recommendations, where necessary)
- (c) Detailed Analysis of:
 - ✓ Routing Selection and Landings,
 - ✓ Geology,
 - ✓ Climatology
 - ✓ Seismology
 - ✓ Oceanography
 - ✓ Environmental and Man-made factors
 - ✓ Fisheries
 - ✓ Biological Factors
 - ✓ Regulatory Factors
- (d) Burial Assessment and Estimated External Aggression Risk
- (e) Route Recommendations (RPLs and SLDs etc)
- (f) Survey Recommendations
- (g) Initial Cable Engineering Recommendations
- (h) Relevant photographs, diagrams and charts
- (i) List of all persons and organisations (plus contact details) consulted during the DTS
- (j) Bibliography of all research material and advice.

The report contents should include:

- All the information gathered during the desk study
- The provisional cable route in the form of both a physical description and route position list that has been developed during the initial conceptual system design and desk study phases of system planning. The provisional route would also be plotted on the system planning charts showing all route alter course points.

- Definition of provisional cable quantities and cable engineering including provisional cable armouring schemes.
- Full detailed description of the cable landing sites (including photographs and diagrams).
- Full details of route permitting issues and procedures including the status of routing negotiations (including contact details for the relevant entities). Estimated times to obtain the various permits should be indicated wherever feasible.
- Definition of detailed route survey procedures and scope of work, which should be based on the most appropriate technical approach that addresses the prevailing physical conditions of the route and the cable protection and installation strategies, recommended in the report.

2.6.4 Digital Format of DTS Report

The Desktop Study Report shall be provided in a digital version, including all text, tables, photographs and diagrams. Consideration should be given to producing digital copies, including photographs, drawings, etc. in a machine independent universal platform such as Adobe's Acrobat™ software. Database and spreadsheet items should also be provided in ODBC (Object Database Connectivity) compliant formats such as Access™, Excel™ and Lotus™.

The ideal platform for displaying and manipulating diverse datasets simultaneously (as well as being a data management system) is a Geographical Information System that does not rely on data transfer to software specific formats. Such GIS systems should be able to read/write ODBC, SQL and Oracle™ databases and related data items. The digital copies should be provided on CD or DVD format which can be read using any IBM™ compatible PC equipped with the above mentioned software.

2.6.5 DTS Report Quantities

It is recommended that consideration be given to the requirements of the cable system supplier when determining the required number of copies of each DTS report.

2.7 Charting Requirements

2.7.1 Description

The DTS shall include a series of north up, adjoining, overlapping charts which should include data presentations showing the proposed cable route, bathymetry contours, geologic interpretations (particularly in areas of proposed burial), existing cables and other pertinent features. Any features identified on the charts shall be annotated in terms of scale, composition and with an appropriate interpretation. The charts should exhibit the following features:

- (a) All charts should show latitude and longitude, graduated in degrees, minutes and decimal minutes. It is recommended that Mercator Projection charts are used for overview and long line segments whilst Universal Transversal Mercator and Lambert Conformal Conic

Projections are used for detail and short leg charts. Note that in some areas, such as Landings, the charts of the cable route may also be required in the National Mapping Projections and Spheroids required for the particular location. Wherever possible, however, one projection should ideally be used throughout the DTS to avoid complications and confusion arising from datum transformations.

- (b) Each chart shall have appropriate title boxes on each of its co-registered parts. Each title box shall include at least:
- ✓ Title (including cable system name and landing points)
 - ✓ Projection
 - ✓ Central meridian specific to that chart
 - ✓ Datum
 - ✓ Scale presented as both a representative fraction and as a linear scale in kilometres (km)
 - ✓ Chart production date
 - ✓ Project identification
 - ✓ Chart key including a suitably scaled overview of the geographic region and the locations of bordering charts. The chart key shall also show the geographic limits of the specific chart
 - ✓ Chart notes
 - ✓ Chart legend
 - ✓ Names of Purchasers
 - ✓ Contractor's name and contact details
 - ✓ A separate chart(s) of the landing that shall identify navigational and other information pertinent to the anchoring/cable landing operations shall be provided. These charts shall extend to at least the 20m water depth and include nearby terrestrial landmarks that may be of assistance in positioning the ship while the cable "shore-end" is landed.

2.7.2 Chart Scales

Recommended chart scales required for various regions along the route are summarised in the table below. Specific requirements should be agreed between the DTS contractor and client prior to contract signing.

<u>Zone</u>	<u>Chart Scale</u>
(a) Overview chart for the whole route	Best Fit
(b) A series of charts for the whole route (to minimum of 1:100,000 as appropriate in order to identify bathymetric features)	1:500,000
(c) Terminal site to 20 metres water depth (including landfall sketch map, at any scale)	1:5,000

(d) Remainder of continental shelf

1:25,000

3. REFERENCES

Document Number	Title
ICPC Recommendation No 2	Recommended Routing & Reporting Criteria For Cables in Proximity to Others

4. DEFINITIONS

The following words, acronyms and abbreviations are referred to in this document.

Term	Definition
DTS	Desktop Study (also known as a Cable Route Study)

5. ATTACHMENTS

Document Number	Title
Nil	

6. ACKNOWLEDGEMENTS

This document has been produced with the kind assistance of the Submarine Cable Improvement Group (<http://www.scig.net/>) and representatives from the Marine Survey Industry.